

[72.936888][T276] this type is not correct!
[75.946199][T276] this type is not correct!

mek_8q:/ # [76.235140][T1] init: starting service 'vendor.gnss_service'...

mek_8q:/ # [76.305265][T247] type=1400 audit(1688627680.124:93): avc: denied { read } for comm="android.hardware" name="vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1

[76.328916][T247] type=1400 audit(1688627680.124:94): avc: denied { write } for comm="android.hardware" name="vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1

[76.333145][T1] init: Service 'vendor.gnss_service' (pid 2664) exited with status 1

[76.359170][T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2664) process group...

[76.361011][T247] type=1400 audit(1688627680.124:95): avc: denied { open } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1

[76.370360][T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2664 in 0ms

[76.397100][T247] type=1400 audit(1688627680.124:96): avc: denied { ioctl } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 ioctlcmd=0x6209 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1

[76.424938][T247] type=1400 audit(1688627680.124:97): avc: denied { map } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1

mek_8q:/ #

mek_8q:/ # logcat -[78.954897][T276] this type is not correct!

b radio

[80.970900][T239] logd: logdr: UID=0 GID=0 PID=2897 b tail=0 logMask=2 pid=0 start=0ns deadline=0ns

----- beginning of radio

07-06 07:13:47.370 509 509 D RILD : **RIL Daemon Started**

07-06 07:13:47.371 509 509 D RILD : **RILd param count=3**

07-06 07:13:47.423 509 509 D RILD : RIL_Init argc = 3 clientId = 0

07-06 07:13:47.424 509 509 D RILC : Quectel RIL Version: Quectel_Android_RIL_Driver_V3.5.49

07-06 07:13:47.426 509 509 D RIL_READ_CONF: since '/system/etc/ql-ril.conf' doesn't exist using '/vendor/etc/ql-ril.conf' but it still doesn't exist program panic here!

07-06 07:13:47.426 509 509 D RILC : [ro.build.version.release]: [13]

07-06 07:13:47.426 509 509 D RILC : Android Version: 130, RIL_VERSION: 12 / 12

07-06 07:13:47.437 509 509 D RILC : __getIRadioVersion:652 IRadioVersion:5

07-06 07:13:47.438 509 509 D RILC : [ro.build.description]: [mek_8q_car-userdebug 13 TP1A.221005.002 eng.zumi.20230705.105655 dev-keys]

07-06 07:13:47.438 509 509 D RILC : [ro.hardware]: [nxp]

07-06 07:13:47.438 509 509 D RILC : selinux maybe set Enforcing mode, use command getenforce to check

07-06 07:13:47.438 509 509 D RILC : selinux maybe set Enforcing mode, use command "setenforce 0" to disable

07-06 07:13:47.438 509 509 I RILC : clientId = 0

07-06 07:13:47.440 509 509 D RILD : RIL_Init rillnit completed

07-06 07:13:47.440 509 509 I RILC : Quectel_Android_Libril_v1.2.7

07-06 07:13:47.440 509 509 I RILC : SIM_COUNT: 1

07-06 07:13:47.440 509 509 E RILC : RIL_register: RIL version 12

07-06 07:13:47.440 509 509 I RILC : s_registerCalled flag set, 1

07-06 07:13:47.440 509 509 I RILC : radio::registerService

07-06 07:13:47.441 509 509 D RIL_SERVICE_1_2: RadiImpl_1_2::RadiImpl_1_2()

07-06 07:13:47.442 509 509 I RIL_SERVICE_1_3: RadiImpl_1_3()

```
07-06 07:13:47.442 509 509 D RIL_SERVICE_1_4: RadiImpl_1_4()
07-06 07:13:47.442 509 509 D rild : new RadiImpl_1_5
07-06 07:13:47.442 509 509 D RIL_SERVICE_1_5: RadiImpl_1_5::registerAsService(slot1)
07-06 07:13:47.447 509 536 I RILC : mainLoop Start
07-06 07:13:47.450 509 536 D RILU : vendor is 0x1b4b
07-06 07:13:47.451 509 536 D RILU : device is 0x2b42
07-06 07:13:47.451 509 536 D RILU : *****1*****
07-06 07:13:47.451 509 536 D RILU : *****1*****
07-06 07:13:47.451 509 536 D RILU : *****1*****
07-06 07:13:47.451 509 536 D RILU : *****1*****
07-06 07:13:47.451 509 536 D RILU : vendor is 0x1957
07-06 07:13:47.452 509 536 D RILU : device is 0x0000
07-06 07:13:47.452 509 536 D RILU : *****1*****
07-06 07:13:47.452 509 536 D RILU : *****1*****
07-06 07:13:47.452 509 536 D RILU : *****1*****
07-06 07:13:47.452 509 536 D RILU : *****1*****
07-06 07:13:47.452 509 536 D RILU : find_pci_device is 0
07-06 07:13:47.452 509 536 D RILC : PCI can't find [ 81.249438][ T1] init: starting service 'vendor.gnss_service'...
at device
07-06 07:13:47.453 509 536 D RILC : USB can't find at device
07-06 07:13:47.458 509 509 D RIL_SERVICE_1_1: status = -2147483648
07-06 07:13:47.458 509 509 I RILC : RILHIDL called registerService
07-06 07:13:47.458 509 509 D RILD : RIL_Init RIL_register completed
07-06 07:13:47.458 509 509 D RILD : RIL_register_socket started
07-06 07:13:47.458 509 509 D RIL_UIM_SOCKET: Adding socket with id: 0
07-06 07:13:47.458 509 509 D RILD : RIL_register_socket completed
07-06 07:13:48.440 509 535 D RILC : dlopen /vendor/lib64/hw/radio.quectel.module.so failed: dlopen failed: library "/vendor/lib64/hw/radio.quectel.module.so" not found
07-06[ 81.316492][ T247] type=1400 audit(1688627685.136:98): avc: denied { read } for comm="android.hardware" name="vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1
07:13:50.453 509 536 D RILU : vendor is 0x1b4b
07-06 07:[ 81.326170][ T1] init: Service 'vendor.gnss_service' (pid 2899) exited with status 1
13:50.454 509 536 D RILU : device is 0x2b42
07-06 07:13:5[ 81.342582][ T247] type=1400 audit(1688627685.136:99): avc: denied { write } for comm="android.hardware" name="vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1
[ 81.355367][ T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2899) process group...
0.454 509 536 D RILU : *****1*****[ 81.383345][ T247] type=1400 audit(1688627685.136:100): avc: denied { open } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1

07-06 07:13:50.454 509 536 D RILU : *****1*****[ 81.392388][ T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2899 in 0ms
*****
07-06 07:13:50.454 509 536 D RILU : *****[ 81.420612][ T247] type=1400 audit(1688627685.136:101): avc: denied { ioctl } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 ioctlcmd=0x6209 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1
*****1*****
07-06 07:13:50.454 509 536 D [ 81.464800][ T247] type=1400 audit(1688627685.136:102): avc: denied { map } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1
```

RILU : *****1*****
07-06 07:13:50.454 509 536 D RILU : vendor is 0x1957
07-06 07:13:50.454 509 536 D RILU : device is 0x0000
07-06 07:13:50.454 509 536 D RILU : *****1*****
07-06 07:13:50.454 509 536 D RILU : *****1*****
07-06 07:13:50.454 509 536 D RILU : *****1*****
07-06 07:13:50.454 509 536 D RILU : *****1*****
07-06 07:13:50.454 509 536 D RILU : find_pci_device is 0
07-06 07:13:50.454 509 536 D RILC : PCI can't find at device
07-06 07:13:50.455 509 536 D RILC : USB can't find at device
07-06 07:13:53.455 509 536 D RILU : vendor is 0x1b4b
07-06 07:13:53.455 509 536 D RILU : device is 0x2b42
07-06 07:13:53.455 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : vendor is 0x1957
07-06 07:13:53.456 509 536 D RILU : device is 0x0000
07-06 07:13:53.456 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : *****1*****
07-06 07:13:53.456 509 536 D RILU : find_pci_device is 0
07-06 07:13:53.456 509 536 D RILC : PCI can't find at device
07-06 07:13:53.456 509 536 D RILC : USB can't find at device
07-06 07:13:56.457 509 536 D RILU : vendor is 0x1b4b
07-06 07:13:56.457 509 536 D RILU : device is 0x2b42
07-06 07:13:56.457 509 536 D RILU : *****1*****
07-06 07:13:56.457 509 536 D RILU : *****1*****
07-06 07:13:56.457 509 536 D RILU : *****1*****
07-06 07:13:56.457 509 536 D RILU : *****1*****
07-06 07:13:56.458 509 536 D RILU : vendor is 0x1957
07-06 07:13:56.458 509 536 D RILU : device is 0x0000
07-06 07:13:56.458 509 536 D RILU : *****1*****
07-06 07:13:56.458 509 536 D RILU : *****1*****
07-06 07:13:56.458 509 536 D RILU : *****1*****
07-06 07:13:56.458 509 536 D RILU : *****1*****
07-06 07:13:56.458 509 536 D RILU : find_pci_device is 0
07-06 07:13:56.458 509 536 D RILC : PCI can't find at device
07-06 07:13:56.458 509 536 D RILC : USB can't find at device
07-06 07:13:59.459 509 536 D RILU : vendor is 0x1b4b
07-06 07:13:59.459 509 536 D RILU : device is 0x2b42
07-06 07:13:59.459 509 536 D RILU : *****1*****
07-06 07:13:59.459 509 536 D RILU : *****1*****
07-06 07:13:59.459 509 536 D RILU : *****1*****
07-06 07:13:59.459 509 536 D RILU : *****1*****
07-06 07:13:59.460 509 536 D RILU : vendor is 0x1957
07-06 07:13:59.460 509 536 D RILU : device is 0x0000
07-06 07:13:59.460 509 536 D RILU : *****1*****
07-06 07:13:59.460 509 536 D RILU : *****1*****
07-06 07:13:59.460 509 536 D RILU : *****1*****
07-06 07:13:59.460 509 536 D RILU : *****1*****
07-06 07:13:59.460 509 536 D RILU : find_pci_device is 0
07-06 07:13:59.460 509 536 D RILC : PCI can't find at device
07-06 07:13:59.460 509 536 D RILC : USB can't find at device

07-06 07:14:02.461 509 536 D RILU : vendor is 0x1b4b
07-06 07:14:02.461 509 536 D RILU : device is 0x2b42
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.461 509 536 D RILU : vendor is 0x1957
07-06 07:14:02.461 509 536 D RILU : device is 0x0000
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.461 509 536 D RILU : *****1*****
07-06 07:14:02.462 509 536 D RILU : find_pci_device is 0
07-06 07:14:02.462 509 536 D RILC : PCI can't find at device
07-06 07:14:02.462 509 536 D RILC : USB can't find at device
07-06 07:14:04.910 599 599 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:05.462 509 536 D RILU : vendor is 0x1b4b
07-06 07:14:05.463 509 536 D RILU : device is 0x2b42
07-06 07:14:05.463 509 536 D RILU : *****1*****
07-06 07:14:05.463 509 536 D RILU : *****1*****[81.962987][T276] this type is not
correct!

07-06 07:14:05.463 509 536 D RILU : *****1*****
07-06 07:14:05.463 509 536 D RILU : *****1*****
07-06 07:14:05.463 509 536 D RILU : vendor is 0x1957
07-06 07:14:05.464 509 536 D RILU : device is 0x0000
07-06 07:14:05.464 509 536 D RILU : *****1*****
07-06 07:14:05.464 509 536 D RILU : *****1*****
07-06 07:14:05.464 509 536 D RILU : *****1*****
07-06 07:14:05.464 509 536 D RILU : *****1*****
07-06 07:14:05.464 509 536 D RILU : find_pci_device is 0
07-06 07:14:05.464 509 536 D RILC : PCI can't find at device
07-06 07:14:05.464 509 536 D RILC : USB can't find at device
07-06 07:14:06.778 599 717 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:07.857 599 718 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:07.886 599 599 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:07.997 599 599 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:08.037 599 616 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigL
oader is null
07-06 07:14:08.074 599 599 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:08.165 599 599 D TelephonyRegistry: systemRunning register for intents
07-06 07:14:08.465 509 536 D RILU : vendor is 0x1b4b
07-06 07:14:08.465 509 536 D RILU : device is 0x2b42
07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : vendor is 0x1957
07-06 07:14:08.465 509 536 D RILU : device is 0x0000

07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : *****1*****
07-06 07:14:08.465 509 536 D RILU : find_pci_device is 0
07-06 07:14:08.465 509 536 D RILC : PCI can't find at device
07-06 07:14:08.466 509 536 D RILC : USB can't find at device
07-06 07:14:08.968 599 624 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:10.197 599 599 D TelephonyRegistry: notifyCellLocationForSubscriber: subId=214748364
7 cellIdentity=null
07-06 07:14:10.385 899 899 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigL
oader is null
07-06 07:14:10.397 599 764 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:10.545 919 919 D TelephonyComponentFactory: validated paths: null
07-06 07:14:10.545 919 919 D TelephonyComponentFactory: Total components injected: 0
07-06 07:14:10.546 919 919 D TDC : updateOrInsert: inserting: Modem { uuid=modem, state=0, rilM
odel=0, rat={}, maxActiveVoiceCall=1, maxActiveDataCall=1, maxStandby=1 }
07-06 07:14:10.546 919 919 D TDC : updateOrInsert: inserting: Sim { uuid=sim, modemUuid=mode
m, state=0 }
07-06 07:14:10.550 919 919 D PersistAtomsStorage: PersistAtoms file not found
07-06 07:14:10.554 919 919 D PersistAtomsStorage: created new PersistAtoms
07-06 07:14:10.562 919 919 D MetricsCollector: registered
07-06 07:14:10.565 919 919 D CdmaSSM : subscriptionSource from settings: 0
07-06 07:14:10.566 919 919 I PhoneFactory: Cdma Subscription set to 0
07-06 07:14:10.566 919 919 I PhoneFactory: Network Mode set to 33
07-06 07:14:10.567 919 919 D RILJ : RIL: init allowedNetworkTypes=916479 cdmaSubscription=0) [
PHONEnull]
07-06 07:14:10.647 919 919 E RILJ : getRadioServiceProxy: set MODEM for slot1 as disabled [PHO
NE0]
07-06 07:14:10.647 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.658 919 919 E RILJ : getRadioProxy: set mRadioProxy for slot1 as disabled [PHONE
0]
07-06 07:14:10.658 919 919 E RILJ : getRadioProxy: mRadioProxy == null [PHONE0]
07-06 07:14:10.675 919 919 E RILJ : getRadioServiceProxy: set DATA for slot1 as disabled [PHONE
0]
07-06 07:14:10.675 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.692 919 919 E RILJ : getRadioServiceProxy: set MESSAGING for slot1 as disabled [
PHONE0]
07-06 07:14:10.692 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.692 919 919 E RILJ : getRadioServiceProxy: MODEM for slot1 is disabled [PHONE0]
07-06 07:14:10.692 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.707 919 919 E RILJ : getRadioServiceProxy: set NETWORK for slot1 as disabled [P
HONE0]
07-06 07:14:10.707 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.722 919 919 E RILJ : getRadioServiceProxy: set SIM for slot1 as disabled [PHONE0]
07-06 07:14:10.722 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.736 919 919 E RILJ : getRadioServiceProxy: set VOICE for slot1 as disabled [PHON
E0]
07-06 07:14:10.736 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.737 919 919 D RILJ : Radio HAL version: 1.0 [PHONE0]
07-06 07:14:10.741 919 919 D UiccController: Creating UiccController
07-06 07:14:10.741 919 919 D UiccController: config_num_physical_slots = 1
07-06 07:14:10.767 919 919 D PinStorage: KeyStore: alias PinStorage_longTerm_always_key exists

07-06 07:14:10.767 919 919 D PinStorage: onDeviceReady
07-06 07:14:10.777 919 919 D PinStorage: KeyStore: alias PinStorage_shortTerm_key does not exist -
Nothing to do
07-06 07:14:10.794 919 919 I PhoneFactory: Creating SubscriptionController
07-06 07:14:10.829 919 919 D SubscriptionController: [SubscriptionController] init by Context
07-06 07:14:10.833 919 919 I PhoneFactory: Creating Phone with type = 1 phoneId = 0
07-06 07:14:10.834 919 919 D TelephonyTester: register for intent action=com.android.internal.telepho
ny.action_detached
07-06 07:14:10.834 919 919 D TelephonyTester: register for intent action=com.android.internal.telepho
ny.action_attached
07-06 07:14:10.835 919 919 D TelephonyTester: register for intent action=com.android.internal.telepho
ny.TestServiceState
07-06 07:14:10.835 919 919 D TelephonyTester: register for intent action=com.android.internal.telepho
ny.TestChangeNumber
07-06 07:14:10.837 919 919 D Phone : mDoesRilSendMultipleCallRing=true
07-06 07:14:10.838 919 919 D Phone : mCallRingDelay=3000
07-06 07:14:10.851 919 919 E RILJ : getRadioProxy: mRadioProxy for slot1 is disabled [PHONE0]
07-06 07:14:10.851 919 919 E RILJ : getRadioProxy: mRadioProxy == null [PHONE0]
07-06 07:14:10.854 919 919 D SmsDispatchersController: SmsDispatchersController created
07-06 07:14:10.858 919 919 D SMSDispatcher: SMSDispatcher: ctor mSmsCapable=true format=unkn
own mSmsSendDisabled=false
07-06 07:14:10.861 919 919 D SMSDispatcher: SMSDispatcher: ctor mSmsCapable=true format=3gpp
2 mSmsSendDisabled=false
07-06 07:14:10.861 919 919 D CdmaSMSDispatcher: CdmaSMSDispatcher created
07-06 07:14:10.866 919 919 E WAP PUSH: bindService() for wappush manager failed
07-06 07:14:10.870 919 919 D GsmInboundSmsHandler: created InboundSmsHandler
07-06 07:14:10.885 919 1083 D GsmInboundSmsHandler: StartupState.enter: entering StartupState
07-06 07:14:10.890 919 919 E WAP PUSH: bindService() for wappush manager failed
07-06 07:14:10.903 919 919 D CdmaInboundSmsHandler: created InboundSmsHandler
07-06 07:14:10.914 919 919 D SMSDispatcher: SMSDispatcher: ctor mSmsCapable=true format=3gpp
mSmsSendDisabled=false
07-06 07:14:10.915 919 919 D GsmSMSDispatcher: GsmSMSDispatcher created
07-06 07:14:10.917 919 1085 D CdmaInboundSmsHandler: StartupState.enter: entering StartupState
07-06 07:14:10.920 919 1083 D GsmInboundSmsHandler: StartupState.processMessage: processing E
VENT_START_ACCEPTING_SMS
07-06 07:14:10.921 919 1083 D GsmInboundSmsHandler: IdleState.enter: entering IdleState
07-06 07:14:10.921 919 1083 D GsmInboundSmsHandler: IdleState.processMessage: processing EVE
NT_RELEASE_WAKELOCK
07-06 07:14:10.922 919 1085 D CdmaInboundSmsHandler: StartupState.processMessage: processing
EVENT_START_ACCEPTING_SMS
07-06 07:14:10.922 919 1085 D CdmaInboundSmsHandler: IdleState.enter: entering IdleState
07-06 07:14:10.922 919 1085 D CdmaInboundSmsHandler: IdleState.processMessage: processing EV
ENT_RELEASE_WAKELOCK
07-06 07:14:10.923 919 1083 D GsmInboundSmsHandler: IdleState.processMessage: EVENT_RELEA
SE_WAKELOCK: mWakeLock released
07-06 07:14:10.926 919 1085 D CdmaInboundSmsHandler: IdleState.processMessage: EVENT_RELE
ASE_WAKELOCK: mWakeLock released
07-06 07:14:10.926 919 919 D CdmaSSM : subscriptionSource from settings: 0
07-06 07:14:10.926 919 919 D CdmaSSM : cdmaSSM constructor: 0
07-06 07:14:10.933 919 919 D GsmCdmaPhone: [0] Precise phone type 1
07-06 07:14:10.934 919 919 D RILJ : setPhoneType=1 old value=0 [PHONE0]
07-06 07:14:10.938 919 919 D CarrierActionAgent: [0]Creating CarrierActionAgent
07-06 07:14:10.939 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigL
oader is null
07-06 07:14:10.943 919 919 D ANM-0 : operates in legacy mode.

07-06 07:14:10.945 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigLoader is null
07-06 07:14:10.956 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigLoader is null
07-06 07:14:10.958 599 656 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOccurred==false no callback
07-06 07:14:10.961 919 919 D NRM-C-0 : registerForNetworkRegistrationInfoChanged
07-06 07:14:10.968 919 919 D NitzStateMachineImpl: handleNetworkUnavailable: mLatestNitzSignal was already null. Nothing to do.
07-06 07:14:10.970 919 919 E RILJ : getRadioServiceProxy: NETWORK for slot1 is disabled [PHONE0]
07-06 07:14:10.971 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:10.972 919 919 D SST : [0] notifyVoiceRegStateRilRadioTechnologyChanged: vrs=1 rat=0
07-06 07:14:10.974 599 613 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOccurred==false no callback
07-06 07:14:10.977 919 919 D Phone : [0] SubId-1,get allowed network types user: value = GPRS|EDGE|UMTS|CDMA|CDMA - EvDo rev. 0|CDMA - EvDo rev. A|CDMA - 1xRTT|HSDPA|HSUPA|HSPA|CDMA - EvDo rev. B|LTE|CDMA - eHRPD|HSPA+|GSM|TD_SCDMA|LTE_CA|NR
07-06 07:14:10.978 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigLoader is null
07-06 07:14:10.981 599 656 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOccurred==false no callback
07-06 07:14:11.007 919 919 D EmergencyNumberTracker: asset emergency database is loaded. Ver: 1 Phone Id: 0
07-06 07:14:11.009 919 919 E EmergencyNumberTracker: Cache ota emergency database IOException: java.io.FileNotFoundException: /data/misc/emergencynumberdb/emergency_number_db: open failed: ENOENT (No such file or directory)
07-06 07:14:11.009 919 919 D EmergencyNumberTracker: Using Asset Emergency database. Version: 1
07-06 07:14:11.030 919 919 D DNC-0 : DataNetworkController created.
07-06 07:14:11.034 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigLoader is null
07-06 07:14:11.036 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigLoader is null
07-06 07:14:11.040 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigLoader is null
07-06 07:14:11.050 919 919 D DCM-0 : DataConfigManager created.
07-06 07:14:11.053 919 919 W CarrierConfigManager: Error getting config for subId -1 ICarrierConfigLoader is null
07-06 07:14:11.067 919 919 D DCM-0 : Data config updated. Config is not carrier specific.
07-06 07:14:11.071 919 919 D DSMGR-0 : DataSettingsManager created.
07-06 07:14:11.077 919 919 D SubscriptionController: Valid row not present in db
07-06 07:14:11.078 919 919 D SubscriptionController: getSubscriptionProperty Query value = null
07-06 07:14:11.082 919 919 D DSRM-0 : DataStallRecoveryManager created.
07-06 07:14:11.086 919 919 D CarrierResolver: Creating CarrierResolver[0]
07-06 07:14:11.092 919 919 D SST : [0] notifyVoiceRegStateRilRadioTechnologyChanged: vrs=1 rat=0
07-06 07:14:11.106 919 919 I GsmCdmaPhone: [0] updateTtyMode ttyMode=0
07-06 07:14:11.107 919 919 E RILJ : getRadioServiceProxy: VOICE for slot1 is disabled [PHONE0]
07-06 07:14:11.107 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:11.109 919 919 I GsmCdmaPhone: [0] updateUiTtyMode ttyMode=0
07-06 07:14:11.109 919 919 D CallManager: registerPhone(GSM Handler (com.android.internal.telephony.GsmCdmaPhone) {17c6de})
07-06 07:14:11.111 599 656 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc

curred==false no callback
07-06 07:14:11.112 919 919 D GsmCdmaPhone: [0] GsmCdmaPhone: constructor: sub = 0
07-06 07:14:11.142 919 919 I PhoneFactory: defaultSmsApplication: com.android.car.messenger
07-06 07:14:11.150 919 919 I PhoneFactory: Creating SubInfoRecordUpdater
07-06 07:14:11.151 919 919 D SubscriptionInfoUpdater: Constructor invoked
07-06 07:14:11.171 919 919 I PhoneFactory: IMS is not supported on this device, skipping ImsResolver.
07-06 07:14:11.180 919 919 W FeatureConnector: [InstanceManager, 0] connect: not supported.
07-06 07:14:11.180 919 1093 I ImsManagerIM [0]: connectionUnavailable, reason: 2
07-06 07:14:11.182 599 828 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:11.186 919 919 D PhoneSwitcher: PhoneSwitcher started
07-06 07:14:11.187 919 919 D ProxyController: Constructor - Enter
07-06 07:14:11.190 919 919 D ProxyController: clearTransaction
07-06 07:14:11.190 919 919 D ProxyController: clearTransaction: phoneId=0 status=IDLE
07-06 07:14:11.191 919 919 D ProxyController: Constructor - Exit
07-06 07:14:11.199 599 828 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:11.200 919 919 D TelephonyNetworkFactory[0]: Registering NetworkFactory
07-06 07:14:11.235 599 656 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:11.236 919 919 D CallManager: registerForMmiComplete
07-06 07:14:11.238 919 919 D NitzStateMachineImpl: handleAirplaneModeChanged(false): mLatestNit
zSignal was already null. Nothing to do.
07-06 07:14:11.265 599 764 D TelephonyRegistry: listen oscl: mHasNotifySubscriptionInfoChangedOc
curred==false no callback
07-06 07:14:11.275 919 919 D UiccController: handleMessage: Received RADIO_UNAVAILABLE for p
honeId 0
07-06 07:14:11.275 919 919 D UiccController: EVENT_RADIO_UNAVAILABLE, dispose card
07-06 07:14:11.276 919 919 D Phone : config LCE service failed: com.android.internal.telephony.Co
mmandException: RADIO_NOT_AVAILABLE
07-06 07:14:11.276 919 919 E RILJ : getRadioServiceProxy: VOICE for slot1 is disabled [PHONE0]
07-06 07:14:11.276 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]
07-06 07:14:11.277 919 919 W FeatureConnector: [ImsSmsDispatcher, 0] connect: not supported.
07-06 07:14:11.277 919 919 D GsmSMSDispatcher: GsmSMSDispatcher: subId = -1 slotId = 0
07-06 07:14:11.277 919 919 D GsmCdmaPhone: [0] Event EVENT_RADIO_OFF_OR_NOT_AVAILABLE
LE Received
07-06 07:14:11.277 919 919 D GsmCdmaPhone: [0] EVENT EVENT_RADIO_STATE_CHANGED
07-06 07:14:11.277 919 919 D GsmCdmaPhone: handleRadioPowerStateChange, state= 2
07-06 07:14:11.280 919 919 D SST : [0] EVENT_ICC_CHANGED: SIM absent
07-06 07:14:11.280 919 919 D SST : [0] cancelAllNotifications: mPrevSubId=-1
07-06 07:14:11.282 919 919 D SST : [0] updateSpnDisplayLegacy+
07-06 07:14:11.286 919 919 D SST : [0] updateSpnDisplay: radio is on but out of service, set plmn=
No service'
07-06 07:14:11.287 919 919 D SST : [0] updateSpnDisplay: rawSpn =
07-06 07:14:11.290 919 919 D SST : [0] updateSpnDisplay: updateSpnDisplay: changed sending int
ent, rule=2, showPlmn='true', plmn='No service', showSpn='false', spn='', dataSpn='', subId='-1'
07-06 07:14:11.291 919 919 D SubscriptionManager: putPhoneIdAndSubIdExtra: no valid subs
07-06 07:14:11.293 919 919 D SubscriptionController: [setPlmnSpn] No valid subscription to store info
07-06 07:14:11.294 919 919 D SubscriptionController: notifySubscriptionInfoChanged:
07-06 07:14:11.294 599 764 D TelephonyRegistry: notifySubscriptionInfoChanged: first invocation mRe
cords.size=34
07-06 07:14:11.312 919 919 D SST : [0] updateSpnDisplayLegacy-
07-06 07:14:11.315 919 919 D NRM-C-0 : Trying to bind com.android.phone for transport WWAN
07-06 07:14:11.320 919 919 D SST : [0] setPowerStateToDesired: mDeviceShuttingDown=false, mD

desiredPowerState=true, getRadioState=2, mRadioDisabledByCarrier=false, IMS reg state=false, pending radio off=false

07-06 07:14:11.320 919 919 D SST : [0] pollState: modemTriggered=true, radioState=2

07-06 07:14:11.321 919 919 D NitzStateMachineImpl: handleNetworkUnavailable: mLatestNitzSignal was already null. Nothing to do.

07-06 07:14:11.322 919 919 D SST : [0] Could not set ServiceState channel number. CellIdentity null

07-06 07:14:11.322 919 919 D SST : [0] Poll ServiceState done: oldSS=[{mVoiceRegState=1(OUT_OF_SERVICE), mDataRegState=1(OUT_OF_SERVICE), mChannelNumber=-1, duplexMode()=0, mCellBandwidths=[], mOperatorAlphaLong=null, mOperatorAlphaShort=null, isManualNetworkSelection=false(automatic), getRilVoiceRadioTechnology=0(Unknown), getRilDataRadioTechnology=0(Unknown), mCssIndicator=unsupported, mNetworkId=-1, mSystemId=-1, mCdmaRoamingIndicator=-1, mCdmaDefaultRoamingIndicator=-1, mIsEmergencyOnly=false, isUsingCarrierAggregation=false, mArfcnRsrpBoost=0, mNetworkRegistrationInfos=[NetworkRegistrationInfo{ domain=CS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}, NetworkRegistrationInfo{ domain=PS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}], mNrFrequencyRange=0, mOperatorAlphaLongRaw=null, mOperatorAlphaShortRaw=null, mIsDataRoamingFromRegistration=false, mIsLwlanPreferred=false}] newSS=[{mVoiceRegState=1(OUT_OF_SERVICE), mDataRegState=1(OUT_OF_SERVICE), mChannelNumber=-1, duplexMode()=0, mCellBandwidths=[], mOperatorAlphaLong=null, mOperatorAlphaShort=null, isManualNetworkSelection=false(automatic), getRilVoiceRadioTechnology=0(Unknown), getRilDataRadioTechnology=0(Unknown), mCssIndicator=unsupported, mNetworkId=-1, mSystemId=-1, mCdmaRoamingIndicator=-1, mCdmaDefaultRoamingIndicator=-1, mIsEmergencyOnly=false, isUsingCarrierAggregation=false, mArfcnRsrpBoost=0, mNetworkRegistrationInfos=[NetworkRegistrationInfo{ domain=CS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}, NetworkRegistrationInfo{ domain=PS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}], mNrFrequencyRange=0, mOperatorAlphaLongRaw=null, mOperatorAlphaShortRaw=null, mIsDataRoamingFromRegistration=false, mIsLwlanPreferred=false}] oldMaxDataCalls=1 mNewMaxDataCalls=1 oldReasonDataDenied=-1 mNewReasonDataDenied=-1

07-06 07:14:11.324 919 919 D SST : [0] pollStateDone: hasRegistered = false hasDeregistered = false hasDataAttached = {1=false} hasDataDetached = {1=false} hasDataRegStateChanged = {1=false} hasRilVoiceRadioTechnologyChanged = false hasRilDataRadioTechnologyChanged = {1=false} hasDataTransportPreferenceChanged = false hasChanged = false hasVoiceRoamingOn = false hasVoiceRoamingOff = false hasDataRoamingOn = false hasDataRoamingOff = false hasLocationChanged = false has4gHandoff = false hasMultiApnSupport = false hasLostMultiApnSupport = false hasCssIndicatorChanged = false hasNrFrequencyRangeChanged = false hasNrStateChanged = false hasBandwidthChanged = true hasAirplaneModeOnChanged = false

07-06 07:14:11.325 919 919 D SST : [0] setPowerStateToDesired: mDeviceShuttingDown=false, mDesiredPowerState=true, getRadioState=2, mRadioDisabledByCarrier=false, IMS reg state=false, pending radio off=false

07-06 07:14:11.325 919 919 D SST : [0] pollState: modemTriggered=true, radioState=2

07-06 07:14:11.325 919 919 D NitzStateMachineImpl: handleNetworkUnavailable: mLatestNitzSignal was already null. Nothing to do.

07-06 07:14:11.326 919 919 D SST : [0] Could not set ServiceState channel number. CellIdentity null

07-06 07:14:11.326 919 919 D SST : [0] Poll ServiceState done: oldSS=[{mVoiceRegState=1(OUT_OF_SERVICE), mDataRegState=1(OUT_OF_SERVICE), mChannelNumber=-1, duplexMode()=0, mCellBandwidths=[], mOperatorAlphaLong=null, mOperatorAlphaShort=null, isManualNetworkSelection=false(

automatic), getRilVoiceRadioTechnology=0(Unknown), getRilDataRadioTechnology=0(Unknown), mCssIndicator=unsupported, mNetworkId=-1, mSystemId=-1, mCdmaRoamingIndicator=-1, mCdmaDefaultRoamingIndicator=-1, mIsEmergencyOnly=false, isUsingCarrierAggregation=false, mArfcnRsrpBoost=0, mNetworkRegistrationInfos=[NetworkRegistrationInfo{ domain=CS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}, NetworkRegistrationInfo{ domain=PS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}], mNrFrequencyRange=0, mOperatorAlphaLongRaw=null, mOperatorAlphaShortRaw=null, mIsDataRoamingFromRegistration=false, mIsLwlanPreferred=false] newSS=[{mVoiceRegState=1(OUT_OF_SERVICE), mDataRegState=1(OUT_OF_SERVICE), mChannelNumber=-1, duplexMode()=0, mCellBandwidths=[], mOperatorAlphaLong=null, mOperatorAlphaShort=null, isManualNetworkSelection=false(automatic), getRilVoiceRadioTechnology=0(Unknown), getRilDataRadioTechnology=0(Unknown), mCssIndicator=unsupported, mNetworkId=-1, mSystemId=-1, mCdmaRoamingIndicator=-1, mCdmaDefaultRoamingIndicator=-1, mIsEmergencyOnly=false, isUsingCarrierAggregation=false, mArfcnRsrpBoost=0, mNetworkRegistrationInfos=[NetworkRegistrationInfo{ domain=CS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}, NetworkRegistrationInfo{ domain=PS transportType=WWAN registrationState=UNKNOWN roamingType=NOT_ROAMING accessNetworkTechnology=UNKNOWN rejectCause=0 emergencyEnabled=false availableServices=[] cellIdentity=null voiceSpecificInfo=null dataSpecificInfo=null nrState=NONE rRplmn= isUsingCarrierAggregation=false}], mNrFrequencyRange=0, mOperatorAlphaLongRaw=null, mOperatorAlphaShortRaw=null, mIsDataRoamingFromRegistration=false, mIsLwlanPreferred=false}] oldMaxDataCalls=1 mNewMaxDataCalls=1 oldReasonDataDenied=-1 mNewReasonDataDenied=-1

07-06 07:14:11.327 919 919 D SST : [0] pollStateDone: hasRegistered = false hasDeregistered = false hasDataAttached = {1=false} hasDataDetached = {1=false} hasDataRegStateChanged = {1=false} hasRilVoiceRadioTechnologyChanged = false hasRilDataRadioTechnologyChanged = {1=false} hasDataTransportPreferenceChanged = false hasChanged = false hasVoiceRoamingOn = false hasVoiceRoamingOff = false hasDataRoamingOn =false hasDataRoamingOff = false hasLocationChanged = false has4gHandoff = false hasMultiApnSupport = false hasLostMultiApnSupport = false hasCssIndicatorChanged = false hasNrFrequencyRangeChanged = false hasNrStateChanged = false hasBandwidthChanged = true hasAirplaneModeOnlChanged = false

07-06 07:14:11.328 919 919 D Phone : [0] SubId-1,get allowed network types user: value = GPRS|EDGE|UMTS|CDMA|CDMA - EvDo rev. 0|CDMA - EvDo rev. A|CDMA - 1xRTT|HSDPA|HSUPA|HSPA|CDMA - EvDo rev. B|LTE|CDMA - eHRPD|HSPA+|GSM|TD_SCDMA|LTE_CA|NR

07-06 07:14:11.328 919 919 D PhoneFactory: calculatePreferredNetworkType: phoneId = 0 networkType = 916479

07-06 07:14:11.330 919 919 D SubscriptionController: [getSlotIndex]- subId invalid

07-06 07:14:11.331 919 919 D Phone : [0] Allowed network types for 'carrier' reason is changed by carrier config = GPRS|EDGE|UMTS|CDMA|CDMA - EvDo rev. 0|CDMA - EvDo rev. A|CDMA - 1xRTT|HSDPA|HSUPA|HSPA|CDMA - EvDo rev. B|LTE|CDMA - eHRPD|HSPA+|GSM|TD_SCDMA|LTE_CA

07-06 07:14:11.331 919 919 D Phone : [0] SubId-1,get allowed network types carrier: value = GPRS|EDGE|UMTS|CDMA|CDMA - EvDo rev. 0|CDMA - EvDo rev. A|CDMA - 1xRTT|HSDPA|HSUPA|HSPA|CDMA - EvDo rev. B|LTE|CDMA - eHRPD|HSPA+|GSM|TD_SCDMA|LTE_CA

07-06 07:14:11.331 919 919 I CSST : isNrSupported: carrierConfigEnabled: true, AccessFamilySupported: false, isNrNetworkTypeAllowed: false

07-06 07:14:11.331 919 919 I CSST : PrefNetworkNotification: sendMessage() w/values: ,false,-1,false,false

07-06 07:14:11.333 919 919 I CSST : canceling notifications: 1000

07-06 07:14:11.333 919 919 D Phone : isWifiCallingEnabled =false

07-06 07:14:11.333 919 919 D CSST : isPhoneRegisteredForWifiCalling: false

07-06 07:14:11.333 919 919 D Phone : isWifiCallingEnabled =false

07-06 07:14:11.333 919 919 I CSST : EmergencyNetworkNotification: sendMessage() w/values: ,-1,f

also,false
07-06 07:14:11.334 919 919 I CSST : canceling notifications: 1001
07-06 07:14:11.334 919 919 D Phone : [0] SubId-1,get allowed network types user: value = GPRS|EDGE|UMTS|CDMA|CDMA - EvDo rev. 0|CDMA - EvDo rev. A|CDMA - 1xRTT|HSDPA|HSUPA|HSPA|CDMA - EvDo rev. B|LTE|CDMA - eHRPD|HSPA+|GSM|TD_SCDMA|LTE_CA|NR
07-06 07:14:11.335 919 919 D PhoneFactory: calculatePreferredNetworkType: phoneId = 0 networkType = 916479
07-06 07:14:11.336 919 919 D Phone : [0] Allowed network types for 'carrier' reason is changed by carrier config = GPRS|EDGE|UMTS|CDMA|CDMA - EvDo rev. 0|CDMA - EvDo rev. A|CDMA - 1xRTT|HSDPA|HSUPA|HSPA|CDMA - EvDo rev. B|LTE|CDMA - eHRPD|HSPA+|GSM|TD_SCDMA|LTE_CA
07-06 07:14:11.336 919 919 D Phone : [0] SubId-1,get allowed network types carrier: value = GPRS|EDGE|UMTS|CDMA|CDMA - EvDo rev. 0|CDMA - EvDo rev. A|CDMA - 1xRTT|HSDPA|HSUPA|HSPA|CDMA - EvDo rev. B|LTE|CDMA - eHRPD|HSPA+|GSM|TD_SCDMA|LTE_CA
07-06 07:14:11.336 919 919 I CSST : isNrSupported: carrierConfigEnabled: true, AccessFamilySupported: false, isNrNetworkTypeAllowed: false
07-06 07:14:11.337 919 919 I CSST : PrefNetworkNotification: sendMessage() w/values: ,false,-1,false,false
07-06 07:14:11.337 919 919 I CSST : canceling notifications: 1000
07-06 07:14:11.338 919 919 D Phone : isWifiCallingEnabled =false
07-06 07:14:11.338 919 919 D CSST : isPhoneRegisteredForWifiCalling: false
07-06 07:14:11.338 919 919 D Phone : isWifiCallingEnabled =false
07-06 07:14:11.338 919 919 I CSST : EmergencyNetworkNotification: sendMessage() w/values: ,-1,false,false
07-06 07:14:11.339 919 919 I CSST : canceling notifications: 1001
07-06 07:14:11.339 919 919 D EmergencyNumberTracker: updateRadioEmergencyNumberListAndNotify(): receiving []
07-06 07:14:11.340 919 919 D NetworkTypeController: [0] DefaultState: process EVENT_INITIALIZE
07-06 07:14:11.341 919 1076 E RadiolInterfaceCapabilityController: setupRadiolInterfaceCapabilities: com.android.internal.telephony.CommandException: RADIO_NOT_AVAILABLE
07-06 07:14:11.341 919 1076 E RadiolInterfaceCapabilityController: setupRadiolInterfaceCapabilities: ar.result is null
07-06 07:14:11.466 509 536 D RILU : vendor is 0x1b4b
07-06 07:14:11.467 509 536 D RILU : device is 0x2b42
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : vendor is 0x1957
07-06 07:14:11.467 509 536 D RILU : device is 0x0000
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : *****1*****
07-06 07:14:11.467 509 536 D RILU : find_pci_device is 0
07-06 07:14:11.467 509 536 D RILC : PCI can't find at device
07-06 07:14:11.468 509 536 D RILC : USB can't find at device
07-06 07:14:13.341 919 919 E RadiolInterfaceCapabilityController: getRadiolInterfaceCapabilities: Radio Capabilities not loaded in time
07-06 07:14:13.348 919 919 D NetworkTypeController: [0] mOverrideTimerRules: {connected={mState=connected, mOverrideType=NR_NSA, mPrimaryTimers={}, mSecondaryTimers={}}, not_restricted_rrc_con={mState=not_restricted_rrc_con, mOverrideType=NR_NSA, mPrimaryTimers={}, mSecondaryTimers={}}, legacy={mState=legacy, mOverrideType=NONE, mPrimaryTimers={}, mSecondaryTimers={}}, not_restricted_rrc_idle={mState=not_restricted_rrc_idle, mOverrideType=NR_NSA, mPrimaryTimers={}, mSecondaryTimers={}}, restricted={mState=restricted, mOverrideType=NONE, mPrimaryTimers={}, mSecondaryTimers={}}, connected_mmwave={mState=connected_mmwave, mOverrideType=NR_NSA, mPrimaryTim

ers={}, mSecondaryTimers={})
07-06 07:14:13.349 919 919 D NetworkTypeController: [0] DefaultState: process EVENT_UPDATE
07-06 07:14:13.349 919 919 D NetworkTypeController: [0] Reset timers since preferred network mode
changed.
07-06 07:14:13.350 919 919 D NetworkTypeController: [0] Entering LegacyState
07-06 07:14:13.352 919 919 D DIC-0 : TelephonyDisplayInfo changed from null to TelephonyDisplayI
nfo {network=UNKNOWN, override=NONE}
07-06 07:14:13.368 919 919 D DataService: Data service created
07-06 07:14:13.468 919 919 D SubscriptionController: [getActiveSubscriptionInfo]- subId=-1 subList=[]
subInfo=null
07-06 07:14:13.474 919 919 D DSMGR-0 : mlsDataEnabled=true, prevDataEnabled=false
07-06 07:14:13.474 919 919 D DSMGR-0 : notifyDataEnabledChanged: enabled=true, reason=UNKN
OWN, callingPackage=com.android.phone
07-06 07:14:13.501 919 919 D CarrierResolver: handleMessage: 2
07-06 07:14:13.910 919 919 E CarrierPrivilegesTracker: Unable to find uid for package android.car.clu
ster and user 10
07-06 07:14:14.009 919 963 D SubscriptionController: [getSlotIndex]- subId invalid
07-06 07:14:14.010 919 963 D SubscriptionController: [getSlotIndex]- subId invalid
07-06 07:14:14.016 919 963 D SubscriptionController: [getSlotIndex]- subId invalid
07-06 07:14:14.372 919 919 E CarrierPrivilegesTracker: Unable to find uid for package com.android.pa
cprocessor and user 10
07-06 07:14:14.468 509 536 D RILU : vendor is 0x1b4b
07-06 07:14:14.469 509 536 D RILU : device is 0x2b42
07-06 07:14:14.469 509 536 D RILU : *****1*****
07-06 07:14:14.469 509 536 D RILU : *****1*****
07-06 07:14:14.469 509 536 D RILU : *****1*****
07-06 07:14:14.469 509 536 D RILU : *****1*****
07-06 07:14:14.469 509 536 D RILU : vendor is 0x1957
07-06 07:14:14.470 509 536 D RILU : device is 0x0000
07-06 07:14:14.470 509 536 D RILU : *****1*****
07-06 07:14:14.470 509 536 D RILU : *****1*****
07-06 07:14:14.470 509 536 D RILU : *****1*****
07-06 07:14:14.470 509 536 D RILU : *****1*****
07-06 07:14:14.470 509 536 D RILU : find_pci_device is 0
07-06 07:14:14.470 509 536 D RILC : PCI can't find at device
07-06 07:14:14.470 509 536 D RILC : USB can't find at device
07-06 07:14:14.498 919 919 E CarrierPrivilegesTracker: Unable to find uid for package com.android.ca
r.scripexecutor and user 10
07-06 07:14:15.908 919 919 E CarrierPrivilegesTracker: Unable to find uid for package com.android.pr
oxyhandler and user 10
07-06 07:14:16.049 919 919 E CarrierPrivilegesTracker: Unable to find uid for package com.android.ex
perimentalcar and user 10
07-06 07:14:16.[84.972645][T276] this type is not correct!
071 919 919 E CarrierPrivilegesTracker: Unable to find uid for package com.android.remoteprovisioner
and user 10
07-06 07:14:16.301 919 919 D GsmCdmaPhone: [0] onVoiceRegStateOrRatChanged
07-06 07:14:16.302 919 919 D GsmCdmaPhone: [0] getCsCallRadioTech, current vrs=1, vrat=0
07-06 07:14:16.302 919 919 D GsmCdmaPhone: [0] getCsCallRadioTech, result calcVrat=0
07-06 07:14:16.316 919 919 D TelephonyNetworkFactory[0]: onActivePhoneSwitch
07-06 07:14:16.324 919 919 D DebugService: DebugService DebugService:
07-06 07:14:16.372 919 919 D GsmSMSDispatcher: GsmSMSDispatcher: subId = -1 slotId = 0
07-06 07:14:16.373 919 919 D SST : [0] EVENT_ICC_CHANGED: SIM absent
07-06 07:14:16.373 919 919 D SST : [0] cancelAllNotifications: mPrevSubId=-1
07-06 07:14:16.382 919 919 D SST : [0] updateSpnDisplayLegacy+
07-06 07:14:16.471 919 919 D SST : [0] updateSpnDisplay: radio is on but out of service, set plmn='

No service'

07-06 07:14:16.474 919 919 D SST : [0] updateSpnDisplay: rawSpn =
07-06 07:14:16.474 919 919 D SST : [0] updateSpnDisplayLegacy-
07-06 07:14:16.475 919 919 D CarrierResolver: handleMessage: 2
07-06 07:14:16.475 919 919 D GsmCdmaCallTracker: Event EVENT_POLL_CALLS_RESULT Received
07-06 07:14:16.475 919 919 D GsmCdmaCallTracker: [0] update phone state, old=IDLE new=IDLE
07-06 07:14:16.475 919 919 D ImsSmsDispatcher [0]: ImsManager: connection unavailable, reason=2
07-06 07:14:16.476 919 919 D SST : [0] SubscriptionListener.onSubscriptionInfoChanged
07-06 07:14:16.501 919 919 D Phone : isImsRegistered =false
07-06 07:14:16.506 919 919 E PhoneSubInfoController: getLine1Number phone is null for Subscription
:-1
07-06 07:14:16.688 919 919 D NetworkService: network service created
07-06 07:14:16.695 919 919 D NetworkTypeController: [0] LegacyState: process EVENT_DATA_RAT_
CHANGED
07-06 07:14:16.700 919 919 D NetworkTypeController: [0] Reset timers since 2G and 3G don't need N
R timers.
07-06 07:14:16.701 919 919 D DSM-C-0 : onServiceConnected: ComponentInfo{com.android.phone/c
om.android.internal.telephony.data.CellularDataService}
07-06 07:14:16.821 919 1183 D CellularDataService: Cellular data service created for slot 0
07-06 07:14:16.822 919 919 D PhoneSwitcher: No active subscriptions: resetting preferred phone to 0 f
or emergency
07-06 07:14:16.823 919 919 D PhoneSwitcher: evaluating due to EVENT_DATA_ENABLED_CHANGE
D phone[0] 0->-1
07-06 07:14:16.840 919 919 D PhoneSwitcher: activate 0
07-06 07:14:16.841 919 919 D PhoneSwitcher: Data switch event. subId=-1, state=START, reason=IN
_CALL
07-06 07:14:16.862 919 919 D DSRM-0 : onMobileDataEnabledChanged: DataEnabled:true,DataStall
ed:false
07-06 07:14:16.862 919 919 D DNC-0 : onDataEnabledChanged: enabled=true
07-06 07:14:16.873 919 919 D SmsBroadcastUndelivered: Received broadcast android.intent.action.U
SER_UNLOCKED
07-06 07:14:16.875 919 919 D SmsDispatchersController: Received broadcast android.intent.action.U
SER_UNLOCKED
07-06 07:14:16.882 919 1394 D SmsBroadcastUndelivered: scanning raw table for undelivered messag
es
07-06 07:14:16.893 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST
id=22, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1001 R
equestorUid: 1001 RequestorPkg: com.android.phone UnderlyingNetworks: Null]]
07-06 07:14:16.900 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST
id=7, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1000 Re
questorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]
07-06 07:14:16.901 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST
id=15, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1000 R
equestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]
07-06 07:14:16.902 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST
id=17, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1073 R
equestorUid: 1073 RequestorPkg: com.android.networkstack UnderlyingNetworks: Null]]
07-06 07:14:16.902 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST
id=1, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VPN&NOT_VCN_MANAGED R
equestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]
07-06 07:14:16.902 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [BACKGRO
UND_REQUEST id=2, [Transports: CELLULAR Capabilities: INTERNET&NOT_RESTRICTED&TRUSTE
D&NOT_VPN&NOT_VCN_MANAGED RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks:
Null]]

07-06 07:14:16.903 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=30, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1000 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]

07-06 07:14:16.903 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=25, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10091 RequestorUid: 10091 RequestorPkg: com.android.systemui UnderlyingNetworks: Null]]

07-06 07:14:16.903 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=27, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10091 RequestorUid: 10091 RequestorPkg: com.android.systemui UnderlyingNetworks: Null]]

07-06 07:14:16.903 919 919 D GsmCdmaPhone: [0] EVENT_SUBSCRIPTIONS_CHANGED

07-06 07:14:16.919 919 919 E PhoneSubInfoController: getLine1Number phone is null for Subscription :-1

07-06 07:14:16.937 919 1394 D SmsBroadcastUndelivered: finished scanning raw table in 54 ms

07-06 07:14:17.032 919 1091 D SubscriptionController: [getSlotIndex]- subId invalid

07-06 07:14:17.053 919 919 D NRM-C-0 : service ComponentInfo{com.android.phone/com.android.internal.telephony.CellularNetworkService} for transport WWAN is now connected.

07-06 07:14:17.054 919 919 D DNC-0 : onDataServiceBindingChanged: WWAN data service is bound.

07-06 07:14:17.055 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=32, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1001 RequestorUid: 1001 RequestorPkg: com.android.phone UnderlyingNetworks: Null]]

07-06 07:14:17.057 919 919 D DNC-0 : Re-evaluating 0 unsatisfied network requests in 0 groups, due to DATA_ENABLED_CHANGED

07-06 07:14:17.069 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=22, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1001 RequestorUid: 1001 RequestorPkg: com.android.phone UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.057, evaluation result=null] shouldApply false

07-06 07:14:17.072 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=7, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1000 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.070, evaluation result=null] shouldApply false

07-06 07:14:17.073 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=15, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1000 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.073, evaluation result=null] shouldApply false

07-06 07:14:17.075 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=17, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1073 RequestorUid: 1073 RequestorPkg: com.android.networkstack UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.074, evaluation result=null] shouldApply false

07-06 07:14:17.077 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=1, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VPN&NOT_VCN_MANAGED RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.077, evaluation result=null] shouldApply false

07-06 07:14:17.079 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [BACKGROUND_REQUEST id=2, [Transports: CELLULAR Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VPN&NOT_VCN_MANAGED RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.077, evaluation result=null] shouldApply false

07-06 07:14:17.081 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=30, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid

: 1000 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.079, evaluation result=null] shouldApply false

07-06 07:14:17.082 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=25, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid : 10091 RequestorUid: 10091 RequestorPkg: com.android.systemui UnderlyingNetworks: Null]], mPriority =20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.082, evaluation result=null] shouldApply false

07-06 07:14:17.084 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=27, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid : 10091 RequestorUid: 10091 RequestorPkg: com.android.systemui UnderlyingNetworks: Null]], mPriority =20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.082, evaluation result=null] shouldApply false

07-06 07:14:17.085 919 919 D DRM-0 : Remove all retry and throttling entries, reason=DATA_SERVICE_BOUND

07-06 07:14:17.087 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=32, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid : 1001 RequestorUid: 1001 RequestorPkg: com.android.phone UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:17.085, evaluation result=null] shouldApply false

07-06 07:14:17.093 919 1103 D SubscriptionController: [getSlotIndex]- subId invalid

07-06 07:14:17.471 509 536 D RILU : vendor is 0x1b4b

07-06 07:14:17.471 509 536 D RILU : device is 0x2b42

07-06 07:14:17.471 509 536 D RILU : *****1*****

07-06 07:14:17.471 509 536 D RILU : *****1*****

07-06 07:14:17.471 509 536 D RILU : *****1*****

07-06 07:14:17.471 509 536 D RILU : *****1*****

07-06 07:14:17.472 509 536 D RILU : vendor is 0x1957

07-06 07:14:17.472 509 536 D RILU : device is 0x0000

07-06 07:14:17.472 509 536 D RILU : *****1*****

07-06 07:14:17.472 509 536 D RILU : *****1*****

07-06 07:14:17.472 509 536 D RILU : *****1*****

07-06 07:14:17.472 509 536 D RILU : *****1*****

07-06 07:14:17.472 509 536 D RILU : find_pci_device is 0

07-06 07:14:17.472 509 536 D RILC : PCI can't find at device

07-06 07:14:17.472 509 536 D RILC : USB can't find at device

07-06 07:14:18.311 919 1091 D SubscriptionController: [getSlotIndex]- subId invalid

07-06 07:14:18.558 919 919 D Phone : isImsRegistered =false

07-06 07:14:18.582 919 919 E PhoneSubInfoController: getLine1Number phone is null for Subscription :-1

07-06 07:14:19.530 919 919 E PhoneSubInfoController: getLine1Number phone is null for Subscription :-1

07-06 07:14:20.406 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=34, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10014 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]

07-06 07:14:20.420 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=34, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid : 10014 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:20.407, evaluation result=null] shouldApply false

07-06 07:14:20.474 509 536 D RILU : vendor is 0x1b4b

07-06 07:14:20.474 509 536 D RILU : device is 0x2b42

07-06 07:14:20.474 509 536 D RILU : *****1*****

07-06 07:14:20.474 509 536 D RILU : *****1*****

07-06 07:14:20.474 509 536 D RILU : *****1*****

07-06 07:14:20.474 509 536 D RILU : *****1*****
07-06 07:14:20.474 509 536 D RILU : vendor is 0x1957
07-06 07:14:20.474 509 536 D RILU : device is 0x0000
07-06 07:14:20.474 509 536 D RILU : *****1*****
07-06 07:14:20.474 509 536 D RILU : *****1*****
07-06 07:14:20.474 509 536 D RILU : *****1*****
07-06 07:14:20.474 509 536 D RILU : *****1*****
07-06 07:14:20.474 509 536 D RILU : find_pci_device is 0
07-06 07:14:20.475 509 536 D RILC : PCI can't find at device
07-06 07:14:20.475 509 536 D RILC : USB can't find at device
07-06 07:14:23.057 599 599 D TelephonyRegistry: notifyCellLocationForSubscriber: subId=214748364
7 cellIdentity=null
07-06 07:14:23.476 509 536 D RILU : vendor is 0x1b4b
07-06 07:14:23.476 509 536 D RILU : device is 0x2b42
07-06 07:14:23.477 509 536 D RILU : *****1*****
07-06 07:14:23.477 509 536 D RILU : *****1*****
07-06 07:14:23.477 509 536 D RILU : *****1*****
07-06 07:14:23.477 509 536 D RILU : *****1*****
07-06 07:14:23.477 509 536 D RILU : vendor is 0x1957
07-06 07:14:23.477 509 536 D RILU : device is 0x0000
07-06 07:14:23.477 509 536 D RILU : *****1*****
07-06 07:14:2[86.270057][T1] init: starting service 'vendor.gnss_service'...
3.477 509 536 D RILU : *****1*****
07-06 07:14:23.477 509 536 D RILU : *****1*****
07-06 07:14:23.477 509 536 D RILU : *****1*****
07-06 07:14:23.478 509 536 D RILU : find_pci_device is 0
07-06 07:14:23.478 509 536 D RILC : PCI can't find at device
07-06 07:14:23.479 509 536 D RILC : USB can't find at device
07-06 07:14:26.481 509 536 D RILU : vendor is 0x1b4b
07-06 07:14:26.481 509 536 D RILU : device is 0x2b42
07-06 07:14:26.482 509 536 D RILU : *****1*****
07-06 07:14:26.482 509 536 D RILU : *****1*****[86.339614][T1] init: Service 've
ndor.gnss_service' (pid 2903) exited with status 1

07-06 07:14:26.482 509 536 D RILU : *****1[86.348183][T1] init: Sending signal 9 to serv
ice 'vendor.gnss_service' (pid 2903) process group...

07-06 07:14:26.482 509 536 D RILU : [86.363557][T1] libprocessgroup: Successfully killed proce
ss cgroup uid 1021 pid 2903 in 0ms
*****1*****
07-06 07:14:26.482 509 536 D RILU : vendor is 0x1957
07-06 07:14:26.482 509 536 D RILU : device is 0x0000
07-06 07:14:26.482 509 536 D RILU : *****1*****
07-06 07:14:26.482 509 536 D RILU : *****1*****
07-06 07:14:26.482 509 536 D RILU : *****1*****
07-06 07:14:26.482 509 536 D RILU : *****1*****
07-06 07:14:26.482 509 536 D RILU : *****1*****
07-06 07:14:26.482 509 536 D RILU : find_pci_device is 0
07-06 07:14:26.482 509 536 D RILC : PCI can't find at device
07-06 07:14:26.486 509 536 D RILU : find quectel module /sys/bus/usb/devices/1-1 idVendor=2c7c id
Product=0901
07-06 07:14:26.487 509 536 D RILU : find_usb_device is 1
07-06 07:14:27.489 509 536 D RILU : find /sys/bus/usb/devices/1-1:1.2/ttyUSB0
07-06 07:14:27.490 509 536 D RILU : ttyAT = ttyUSB0
07-06 07:14:27.490 509 536 D RILU : find /sys/bus/usb/devices/1-1:1.7/ttyUSB5
07-06 07:14:27.490 509 536 D RILU : ttyPPP = ttyUSB5

07-06 07:14:27.490 509 536 D RILU : find /sys/bus/usb/devices/1-1:1.3/ttyUSB1
07-06 07:14:27.490 509 536 D RILU : ttyDM = ttyUSB1
07-06 07:14:27.490 509 536 D RILU : find /sys/bus/usb/devices/1-1:1.8/ttyUSB6
07-06 07:14:27.490 509 536 D RILU : ttyGPS = ttyUSB6
07-06 07:14:27.491 509 536 D RILU : find /sys/bus/usb/devices/1-1:1.0/net/usb0
07-06 07:14:27.491 509 536 D RILU : usbnet_adapter = usb0
07-06 07:14:27.492 509 536 D RILU : netcard driver: cdc_ether, driver version: 5.15.71-dirty
07-06 07:14:27.492 509 536 D RILU : ECM = usb0
07-06 07:14:27.492 509 536 D RILC : quectel at port is /dev/ttyUSB0
07-06 07:14:27.492 509 536 D RILU : ql_set_autosuspend, enter...
07-06 07:14:27.492 509 536 D RILU : ro_hardware:nxp
07-06 07:14:27.492 509 536 D RILU : -----2:nxp
07-06 07:14:27.492 509 536 D RILU : -----3:1
07-06 07:14:27.492 509 536 D RILU : -----3:2
07-06 07:14:27.530 509 536 D RILU : echo on > /sys/bus/usb/devices/1-1/power/control
07-06 07:14:27.531 509 536 D RILU : ql_set_autosuspend off
07-06 07:14:27.531 509 536 D RILU : -----3:3
07-06 07:14:27.531 509 536 D RILU : -----3:1
07-06 07:14:27.531 509 536 D RILU : -----3:3
07-06 07:14:27.531 509 536 D RILU : -----3:1
07-06 07:14:27.531 509 536 D RILU : -----3:3
07-06 07:14:27.531 509 536 D RILU : -----3:1
07-06 07:14:27.531 509 536 D RILU : -----3:3
07-06 07:14:27.531 509 536 D RILU : -----4
07-06 07:14:27.531 509 536 D RILC : s_device_path is /dev/ttyUSB0
07-06 07:14:27.548 509 536 D RILC : open device /dev/ttyUSB0 correctly
07-06 07:14:27.549 509 536 E ATC : at_open s_tild_reader = 512644263088
07-06 07:14:27.552 509 535 D ATC : AT> ATE0
07-06 07:14:27.574 509 1840 D ATC : AT< OK
07-06 07:14:27.574 509 535 D ATC : AT> AT+CMEE=1
07-06 07:14:27.595 509 1840 D ATC : AT< OK
07-06 07:14:27.596 509 535 D ATC : AT> ATI
07-06 07:14:27.618 509 1840 D ATC : AT< Quectel
07-06 07:14:27.618 509 1840 D ATC : AT< EC200U
07-06 07:14:27.618 509 1840 D ATC : AT< Revision: EC200UCNAAR02A10M08
07-06 07:14:27.618 509 1840 D ATC : AT< OK
07-06 07:14:27.618 509 535 D RILC : ql_product_version is EC200UCNAAR02A10M08
07-06 07:14:27.618 509 535 D RILC : Quectel Product Revision: EC200UCNAAR02A10M08
07-06 07:14:27.618 509 535 D RILU : ql_set_autosuspend, enter...
07-06 07:14:27.619 509 535 D RILU : ro_hardware:nxp
07-06 07:14:27.619 509 535 D RILU : -----2:nxp
07-06 07:14:27.619 509 535 D RILU : -----3:1
07-06 07:14:27.619 509 535 D RILU : -----3:2
07-06 07:14:27.657 509 535 D RILU : echo on > /sys/bus/usb/devices/1-1/power/control
07-06 07:14:27.657 509 535 D RILU : ql_set_autosuspend off
07-06 07:14:27.657 509 535 D RILU : -----3:3
07-06 07:14:27.657 509 535 D RILU : -----3:1
07-06 07:14:27.657 509 535 D RILU : -----3:3
07-06 07:14:27.657 509 535 D RILU : -----3:1
07-06 07:14:27.657 509 535 D RILU : -----3:3
07-06 07:14:27.657 509 535 D RILU : -----3:1
07-06 07:14:27.657 509 535 D RILU : -----3:3
07-06 07:14:27.657 509 535 D RILU : -----4
07-06 07:14:27.657 509 535 D RILC : UNISOC Platform
07-06 07:14:27.660 509 535 D ATC : AT> AT+QGPSCFG="outport","usbnmea"

07-06 07:14:27.681 509 1840 D ATC : AT< OK
07-06 07:14:27.683 509 535 D ATC : AT> AT+CSUB;+CVERSION
07-06 07:14:27.687 509 1861 D tty2tcp : swap_sources (s:rild-nmea <> c:13) fifo_size=4096
07-06 07:14:27.687 509 1861 D tty2tcp : create_socket_server(rild-nmea)
07-06 07:14:27.687 509 1861 D tty2tcp : local server: rild-nmea sockfd = 16
07-06 07:14:27.688 509 1861 D tty2tcp : create_socket_server(serverfd=16)
07-06 07:14:27.688 509 1861 D tty2tcp : rild_socket_add [1]=16
07-06 07:14:27.692 509 1863 D tty2tcp : open /dev/ttyUSB6 ttyfd = 17
07-06 07:14:27.693 509 1863 D GPS : ql_gps_read_nmea open gps device /dev/ttyUSB6 successful
y, fd = 17
07-06 07:14:27.705 509 1840 D ATC : AT< SubEdition: V07
07-06 07:14:27.705 509 1840 D ATC : AT< VERSION: EC200UCNAAR02A10M08
07-06 07:14:27.705 509 1840 D ATC : AT< Mar 3 2022 09:45:11
07-06 07:14:27.705 509 1840 D ATC : AT< Authors: QCT
07-06 07:14:27.705 509 1840 D ATC : AT< OK
07-06 07:14:27.705 509 535 D ATC : AT> ATE0
07-06 07:14:27.726 509 1840 D ATC : AT< OK
07-06 07:14:27.726 509 535 D ATC : AT> at+cmee=1
07-06 07:14:27.748 509 1840 D ATC : AT< OK
07-06 07:14:27.748 509 535 D ATC : AT> ATS0=0
07-06 07:14:27.769 509 1840 D ATC : AT< OK
07-06 07:14:27.770 509 535 D ATC : AT> AT+QURCCFG="URCPORT","usbat"
07-06 07:14:27.791 509 1840 D ATC : AT< OK
07-06 07:14:27.791 509 535 D ATC : AT> AT&D2
07-06 07:14:27.812 509 1840 D ATC : AT< OK
07-06 07:14:27.812 509 535 D ATC : AT> AT+CMEE=1
07-06 07:14:27.834 509 1840 D ATC : AT< OK
07-06 07:14:27.834 509 535 D ATC : AT> AT+QCFG="ims",1
07-06 07:14:27.859 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:27.859 509 535 D ATC : AT> AT+CREG=2
07-06 07:14:27.881 509 1840 D ATC : AT< OK
07-06 07:14:27.881 509 535 D ATC : AT> AT+CREG=2
07-06 07:14:27.903 509 1840 D ATC : AT< OK
07-06 07:14:27.903 509 535 D ATC : AT> AT+CGREG=2
07-06 07:14:27.925 509 1840 D ATC : AT< OK
07-06 07:14:27.925 509 535 D ATC : AT> AT+CREG=2
07-06 07:14:27.948 509 1840 D ATC : AT< OK
07-06 07:14:27.948 509 535 D ATC : AT> AT+C5GREG=2
07-06 07:14:27.969 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:27.969 509 535 D ATC : AT> AT+QENDC=1
07-06 07:14:27.990 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:27.991 509 535 D ATC : AT> AT^DSCI=1
07-06 07:14:28.012 509 1840 D ATC : AT< OK
07-06 07:14:28.012 509 535 D ATC : AT> AT+CFUN?
07-06 07:14:28.033 509 1840 D ATC : AT< +CFUN: 1
07-06 07:14:28.034 509 1840 D ATC : AT< OK
07-06 07:14:28.034 509 535 D ATC : AT> AT+CPIN?
07-06 07:14:28.055 509 1840 D ATC : AT< +CPIN: READY
07-06 07:14:28.055 509 1840 D ATC : AT< OK
07-06 07:14:28.055 509 535 D ATC : AT> AT+CFUN?
07-06 07:14:28.077 509 1840 D ATC : AT< +CFUN: 1
07-06 07:14:28.077 509 1840 D ATC : AT< OK
07-06 07:14:28.078 509 535 I RILC : [setRadioState]:oldState=1, newState=2
07-06 07:14:28.079 509 1863 D ATC : AT> AT+QGPSXTRA=1
07-06 07:14:28.082 509 535 E RIL_SERVICE_1_1: radioStateChangedInd-0-1: radioService[0]->mRad

ioIndication == NULL
07-06 07:14:28.082 509 535 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_RESPONSE_RADIO
_STATE_CHANGED length:0
07-06 07:14:28.100 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:28.100 509 1863 D ATC : AT> AT+QGPSXTRADATA?
07-06 07:14:28.125 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:28.125 509 1863 E GPS : ql_xtradata_inject_time :0/0/0, 0:0:0
07-06 07:14:28.125 509 1863 D ATC : AT> AT+QGPSXTRA=0
07-06 07:14:28.148 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:28.148 509 535 D ATC : AT> AT+CPIN?
07-06 07:14:28.169 509 1840 D ATC : AT< +CPIN: READY
07-06 07:14:28.169 509 1840 D ATC : AT< OK
07-06 07:14:28.169 509 535 I RILC : [setRadioState]:oldState=2, newState=4
07-06 07:14:28.169 509 535 E RIL_SERVICE_1_1: radioStateChangedInd-0-1: radioService[0]->mRad
ioIndication == NULL
07-06 07:14:28.170 509 535 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_RESPONSE_RADIO
_STATE_CHANGED length:0
07-06 07:14:28.170 509 535 D ATC : AT> AT+QNVFR="/nv/item_files/modem/mmode/ue_usage_se
tting"
07-06 07:14:28.191 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:28.191 509 535 D RILC : ue_function check failed no need to set
07-06 07:14:28.191 509 535 D ATC : AT> AT+QINISTAT
07-06 07:14:28.212 509 1840 D ATC : AT< +QINISTAT: 1
07-06 07:14:28.212 509 1840 D ATC : AT< OK
07-06 07:14:28.212 509 535 D ATC : AT> AT+CSMS=1
07-06 07:14:28.234 509 1840 D ATC : AT< +CSMS: 1,1,1
07-06 07:14:28.234 509 1840 D ATC : AT< OK
07-06 07:14:28.234 509 535 D ATC : AT> AT+CNMI=2,2
07-06 07:14:28.262 509 1840 D ATC : AT< OK
07-06 07:14:28.263 509 535 D ATC : AT> AT+CMGF=0
07-06 07:14:28.284 509 1840 D ATC : AT< OK
07-06 07:14:28.285 509 535 D ATC : AT> AT+CCWA=1
07-06 07:14:28.313 509 1840 D ATC : AT< OK
07-06 07:14:28.313 509 535 D ATC : AT> AT+CMOD=0
07-06 07:14:28.334 509 1840 D ATC : AT< OK
07-06 07:14:28.335 509 535 D ATC : AT> AT+CMUT=0
07-06 07:14:28.356 509 1840 D ATC : AT< OK
07-06 07:14:28.356 509 535 D ATC : AT> AT+CSSN=0,1
07-06 07:14:28.383 509 1840 D ATC : AT< OK
07-06 07:14:28.384 509 535 D ATC : AT> AT+COLP=0
07-06 07:14:28.409 509 1840 D ATC : AT< OK
07-06 07:14:28.409 509 535 D ATC : AT> AT+CSCS="UCS2"
07-06 07:14:28.435 509 1840 D ATC : AT< OK
07-06 07:14:28.435 509 535 D ATC : AT> AT+CUSD=1
07-06 07:14:28.457 509 1840 D ATC : AT< OK
07-06 07:14:28.457 509 535 D ATC : AT> AT+CGEREP=0
07-06 07:14:28.478 509 1840 D ATC : AT< OK
07-06 07:14:28.479 509 535 D ATC : AT> AT+CGEREP=0
07-06 07:14:28.500 509 1840 D ATC : AT< OK
07-06 07:14:28.500 509 535 D ATC : AT> AT+CTZU=1
07-06 07:14:28.521 509 1840 D ATC : AT< OK
07-06 07:14:28.521 509 535 D ATC : AT> AT+CTZR=2
07-06 07:14:28.543 509 1840 D ATC : AT< OK
07-06 07:14:28.543 509 535 E RIL_SERVICE_1_1: simStatusChangedInd: radioService[0]->mRadiIo
ndication == NULL

07-06 07:14:28.543 509 535 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_RESPONSE_SIM_S
TATUS_CHANGED length:0
07-06 07:14:28.544 509 535 D ATC : AT> AT+QCFG="speed"
07-06 07:14:28.565 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:28.565 509 535 D ATC : AT> AT+QNWCFG="lte_pco",2
07-06 07:14:28.586 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:28.587 509 535 D ATC : AT> AT+QIMSCFG="ims_status"
07-06 07:14:28.608 509 1840 D ATC : AT< +CME ERROR: 58
07-06 07:14:28.608 509 535 D SIGNAL_STRENGTH: requestSignalStrength:720 iradio_version = 5
07-06 07:14:28.608 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:14:28.631 509 1840 D ATC : AT< +COPS: 0
07-06 07:14:28.632 509 1840 D ATC : AT< +COPS: 0
07-06 07:14:28.632 509 1840 D ATC : AT< OK
07-06 07:14:28.632 509 535 D ATC : AT> AT+QENG="servingcell"
07-06 07:14:28.655 509 1840 D ATC : AT< +QENG: "servingcell","SEARCH"
07-06 07:14:28.655 509 1840 D ATC : AT< OK
07-06 07:14:28.655 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:14:28.677 509 1840 D ATC : AT< +COPS: 0
07-06 07:14:28.678 509 1840 D ATC : AT< +COPS: 0
07-06 07:14:28.679 509 1840 D ATC : AT< OK
07-06 07:14:28.679 509 535 D RIL_SERVICE_1_4: currentSignalStrengthInd 1948
07-06 07:14:28.679 509 535 E RIL_SERVICE_1_4: currentSignalStrengthInd_1_4: radioService[0]->m
RadioIndication == NULL
07-06 07:14:28.679 509 535 E RIL_SERVICE_1_2: currentSignalStrengthInd_1_2: radioService[0]->m
RadioIndication == NULL
07-06 07:14:28.679 509 535 E RIL_SERVICE_1_1: currentSignalStrengthInd: radioService[0]->mRadio
Indication == NULL
07-06 07:14:28.679 509 535 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_SIGNAL_STRENGT
H length:108
07-06 07:14:29.600 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST
id=36, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10075
RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]
07-06 07:14:29.601 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [R
EQUEST id=36, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid
: 10075 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UN
SATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:29.601, evaluation result=
null] shouldApply false
07-06 07:14:30.179 509 1840 D ATC : AT< +QIND: SMS DONE
07-06 07:14:30.179 509 535 D ATC : AT> AT+CPIN?
07-06 07:14:30.201 509 1840 D ATC : AT< +CPIN: READY
07-06 07:14:30.201 509 1840 D ATC : AT< OK
07-06 07:14:30.201 509 535 I RILC : [setRadioState]:oldState=4, newState=4
07-06 07:14:30.201 509 535 D ATC : AT> AT+QINISTAT
07-06 07:14:30.222 509 1840 D ATC : AT< +QINISTAT: 3
07-06 07:14:30.222 509 1840 D ATC : AT< OK
07-06 07:14:30.223 509 535 D ATC : AT> AT+CSMS=1
07-06 07:14:30.244 509 1840 D ATC : AT< +CSMS: 1,1,1
07-06 07:14:30.244 509 1840 D ATC : AT< OK
07-06 07:14:30.244 509 535 D ATC : AT> AT+CNMI=2,2
07-06 07:14:30.268 509 1840 D ATC : AT< OK
07-06 07:14:30.268 509 535 D ATC : AT> AT+CMGF=0
07-06 07:14:30.291 509 1840 D ATC : AT< OK
07-06 07:14:31.874 919 919 D TelephonyNetworkFactory[0]: onReleaseNetworkFor [NetworkRequest [R
EQUEST id=32, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED
Uid: 1001 RequestorUid: 1001 RequestorPkg: com.android.phone UnderlyingNetworks: Null]], mPriority=

20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:31.872, evaluation result=null] applied false

07-06 07:14:31.976 509 1840 D ATC : AT< +CREG: 1,"046F","0009A1F",7

07-06 07:14:31.976 509 1840 D RILC : RIL_UNSOL_RESPONSE_VOICE_NETWORK_STATE_CHANGED wait sim ready

07-06 07:14:31.976 509 1840 D ATC : AT< +CGREG: 1,"046F","0009A1F",7

07-06 07:14:31.976 509 1840 D RILC : RIL_UNSOL_RESPONSE_VOICE_NETWORK_STATE_CHANGED wait sim ready

07-06 07:14:31.976 509 1840 D ATC : AT< +CEREG: 1,"046F","0009A1F",7

07-06 07:14:31.976 509 1840 D RILC : RIL_UNSOL_RESPONSE_VOICE_NETWORK_STATE_CHANGED wait sim ready

07-06 07:14:31.976 509 1840 D ATC : AT< +CTZE: "+22",0,"2023/07/18,17:26:40"

07-06 07:14:31.977 509 1840 D RILC : 2023 7 18 17 26 40

07-06 07:14:31.978 509 1840 E RIL_SERVICE_1_1: nitzTimeReceivedInd: radioService[0]->mRadioIndication == NULL

07-06 07:14:31.978 509 1840 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_NITZ_TIME_RECEIVED length:22

07-06 07:14:32.108 919 1091 D SubscriptionController: [getSlotIndex]- subId invalid

07-06 07:14:32.421 919 919 E RILJ : getRadioServiceProxy: MODEM for slot1 is disabled [PHONE0]

07-06 07:14:32.421 919 919 E RILJ : getRadioServiceProxy: serviceProxy == null [PHONE0]

07-06 07:14:34.830 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=38, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10087 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]

07-06 07:14:34.832 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=38, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10087 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:34.831, evaluation result=null] shouldApply false

07-06 07:14:34.933 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=40, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10087 RequestorUid: 10087 RequestorPkg: com.android.remoteprovisioner UnderlyingNetworks: Null]]

07-06 07:14:34.944 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=40, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10087 RequestorUid: 10087 RequestorPkg: com.android.remoteprovisioner UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:34.935, evaluation result=null] shouldApply false

07-06 07:14:36.009 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=42, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10043 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]

07-06 07:14:36.010 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=42, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10043 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:36.009, evaluation result=null] shouldApply false

07-06 07:14:36.032 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=44, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10043 RequestorUid: 10043 RequestorPkg: com.android.statementservice UnderlyingNetworks: Null]]

07-06 07:14:36.034 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=44, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 10043 RequestorUid: 10043 RequestorPkg: com.android.statementservice UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:36.032, evaluation result=null] shouldApply false

07-06 07:14:36.661 919 2437 D ONSNetworkScanCtrl: init called

07-06 07:14:36.685 599 828 D TelephonyRegistry: listen ooscl: hasNotifyOpptSubInfoChangedOccurre

d==false no callback
07-06 07:14:36.686 919 2437 D ONSProfileSelector: ONSProfileSelector init complete
07-06 07:14:36.728 919 2437 D ONS : service is enable state true
07-06 07:14:38.547 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:38.569 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:39.571 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:39.592 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:40.533 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=47, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1010075 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]
07-06 07:14:40.535 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=47, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid : 1010075 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:40.533, evaluation result =null] shouldApply false
07-06 07:14:40.594 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:40.615 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:41.617 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:41.638 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:42.622 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=49, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1010043 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]]
07-06 07:14:42.624 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=49, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid : 1010043 RequestorUid: 1000 RequestorPkg: android UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:42.622, evaluation result =null] shouldApply false
07-06 07:14:42.639 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:42.641 919 919 D TelephonyNetworkFactory[0]: got request NetworkRequest [REQUEST id=51, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid: 1010043 RequestorUid: 1010043 RequestorPkg: com.android.statementservice UnderlyingNetworks: Null]]
07-06 07:14:42.643 919 919 D TelephonyNetworkFactory[0]: onNeedNetworkFor [NetworkRequest [REQUEST id=51, [Capabilities: INTERNET&NOT_RESTRICTED&TRUSTED&NOT_VCN_MANAGED Uid : 1010043 RequestorUid: 1010043 RequestorPkg: com.android.statementservice UnderlyingNetworks: Null]], mPriority=20, state=UNSATISFIED, mAttachedDataNetwork=null, isMetered=true, created time=07:14:42.641, evaluation result=null] shouldApply false
07-06 07:14:42.661 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:43.662 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:43.683 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:44.685 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:44.706 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:45.707 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:45.729 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:46.730 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:46.752 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:47.753 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:47.774 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:48.680 509 535 D SIGNAL_STRENGTH: requestSignalStrength:720 iradio_version = 5
07-06 07:14:48.680 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:14:48.704 509 1840 D ATC : AT< +COPS: 0,0,"Airtel",7
07-06 07:14:48.706 509 1840 D ATC : AT< +COPS: 0,1,"Airtel",7
07-06 07:14:48.706 509 1840 D ATC : AT< OK
07-06 07:14:48.706 509 535 D ATC : AT> AT+QENG="servingcell"
07-06 07:14:48.731 509 1840 D ATC : AT< +QENG: "servingcell","NOCONN","LTE","FDD",404,45,9A1F,292,240,1,3,3,46F,-83,-9,-58,53,40

07-06 07:14:48.732 509 1840 D ATC : AT< OK
07-06 07:14:48.732 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:14:48.754 509 1840 D ATC : AT< +COPS: 0,0,"Airtel",7
07-06 07:14:48.756 509 1840 D ATC : AT< +COPS: 0,1,"Airtel",7
07-06 07:14:48.756 509 1840 D ATC : AT< OK
07-06 07:14:48.756 509 535 D CELL_INFO: parseServingCell_234G:711 LTE RSRP=-83
07-06 07:14:48.756 509 535 D ATC : AT> AT+CSQ
07-06 07:14:48.778 509 1840 D ATC : AT< +CSQ: 27,99
07-06 07:14:48.778 509 1840 D ATC : AT< OK
07-06 07:14:48.779 509 535 D RADIO_1_4: getSignalStrength_1_4:563 LTE RSRP = -83 RSRQ = -9
07-06 07:14:48.779 509 535 D RIL_SERVICE_1_4: currentSignalStrengthInd 1948
07-06 07:14:48.779 509 535 E RIL_SERVICE_1_4: currentSignalStrengthInd_1_4: radioService[0]->mRadioIndication == NULL
07-06 07:14:48.779 509 535 E RIL_SERVICE_1_2: currentSignalStrengthInd_1_2: radioService[0]->mRadioIndication == NULL
07-06 07:14:48.779 509 535 E RIL_SERVICE_1_1: currentSignalStrengthInd: radioService[0]->mRadioIndication == NULL
07-06 07:14:48.779 509 535 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_SIGNAL_STRENGTH length:108
07-06 07:14:48.779 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:48.800 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:49.802 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:49.823 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:50.477 509 1840 D ATC : AT< +QIND: PB DONE
07-06 07:14:50.477 509 1840 E RILC : RDY !!!
07-06 07:14:50.478 509 535 D ATC : AT> AT+CPIN?
07-06 07:14:50.504 509 1840 D ATC : AT< +CPIN: READY
07-06 07:14:50.504 509 1840 D ATC : AT< OK
07-06 07:14:50.504 509 535 I RILC : [setRadioState]:oldState=4, newState=4
07-06 07:14:50.824 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:50.845 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:51.846 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:51.868 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:52.869 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:52.890 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:53.892 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:53.913 509 1840 D ATC : AT< +CME ERROR: 3
[90.992341][T276] this type is not correct!
07-06 07:14:54.915 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:54.936 509 1840 D ATC : AT< +CME ERROR: 3
[91.288098][T1] init: starting service 'vendor.gnss_service'...
[91.360534][T1] init: Service 'vendor.gnss_service' (pid 2906) exited with status 1
[91.368817][T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2906) process group...
[91.378736][T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2906 in 0ms
07-06 07:14:55.937 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:55.958 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:56.960 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:56.981 509 1840 D ATC : AT< +CME ERROR: 3
[93.999654][T276] this type is not correct!
07-06 07:14:57.982 509 535 D ATC : AT> at+qcfg="aprstlevel"
07-06 07:14:58.003 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:14:59.005 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:14:59.026 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:00.027 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:00.049 509 1840 D ATC : AT< +CME ERROR: 3

```
[ 96.305526][ T1] init: starting service 'vendor.gnss_service'...
[ 96.376890][ T1] init: Service 'vendor.gnss_service' (pid 2907) exited with status 1
[ 96.385033][ T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2907) process group...
[ 96.394894][ T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2907 in 0ms
[ 97.006834][ T276] this type is not correct!
07-06 07:15:01.050 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:01.071 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:02.073 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:02.094 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:03.095 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:03.116 509 1840 D ATC : AT< +CME ERROR: 3
[ 100.014043][ T276] this type is not correct!
07-06 07:15:04.118 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:04.139 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:05.140 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
[ 101.322387][ T1] init: starting service 'vendor.gnss_service'...
07-06 07:15:05.162 509 1840 D ATC : AT< +CME ERROR: 3
[ 101.394855][ T1] init: Service 'vendor.gnss_service' (pid 2908) exited with status 1
[ 101.403023][ T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2908) process group...
[ 101.412895][ T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2908 in 0ms
07-06 07:15:06.163 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:06.184 509 1840 D ATC : AT< +CME ERROR: 3
[ 103.021177][ T276] this type is not correct!
07-06 07:15:07.186 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:07.207 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:08.208 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:08.230 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:08.544 509 535 D RILC : QuectelCheckAndroidFra[ 104.718084][ T247] type=1400 aud
it(1688627708.544:103): avc: denied { search } for comm="rild" name="data" dev="dm-6" ino=98 scontext
=u:r:rild:s0 tcontext=u:object_r:system_data_file:s0:c512,c768 tclass=dir permissive=1
meworkSettingCallback
07-06 07:15:08.616 509 535 D RILC : [ro.radio.noril]: [false]
07-06 07:15:08.779 509 535 D SIGNAL_STRENGTH: requestSignalStrength:720 iradio_version = 5
07-06 07:15:08.779 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:15:08.802 509 1840 D ATC : AT< +COPS: 0,0,"Airtel",7
07-06 07:15:08.804 509 1840 D ATC : AT< +COPS: 0,1,"Airtel",7
07-06 07:15:08.804 509 1840 D ATC : AT< OK
07-06 07:15:08.804 509 535 D ATC : AT> AT+QENG="servingcell"
07-06 07:15:08.829 509 1840 D ATC : AT< +QENG: "servingcell","NOCONN","LTE","FDD",404,45,9
A1F,292,240,1,3,3,46F,-83,-8,-59,65,40
07-06 07:15:08.829 509 1840 D ATC : AT< OK
07-06 07:15:08.829 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:15:08.852 509 1840 D ATC : AT< +COPS: 0,0,"Airtel",7
07-06 07:15:08.854 509 1840 D ATC : AT< +COPS: 0,1,"Airtel",7
07-06 07:15:08.854 509 1840 D ATC : AT< OK
07-06 07:15:08.854 509 535 D CELL_INFO: parseServingCell_234G:711 LTE RSRP=-83
07-06 07:15:08.854 509 535 D ATC : AT> AT+CSQ
07-06 07:15:08.876 509 1840 D ATC : AT< +CSQ: 27,99
07-06 07:15:08.876 509 1840 D ATC : AT< OK
07-06 07:15:08.877 509 535 D RADIO_1_4: getSignalStrength_1_4:563 LTE RSRP = -83 RSRQ = -8
07-06 07:15:08.877 509 535 D RIL_SERVICE_1_4: currentSignalStrengthInd 1948
07-06 07:15:08.877 509 535 E RIL_SERVICE_1_4: currentSignalStrengthInd_1_4: radioService[0]->m
RadiIndication == NULL
07-06 07:15:08.877 509 535 E RIL_SERVICE_1_2: currentSignalStrengthInd_1_2: radioService[0]->m
RadiIndication == NULL
```


07-06 07:15:08.877 509 535 E RIL_SERVICE_1_1: currentSignalStrengthInd: radioService[0]->mRadio Indication == NULL
07-06 07:15:08.877 509 535 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_SIGNAL_STRENGTH length:108
07-06 07:15:09.230 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:09.252 509 1840 D ATC : AT< +CME ERROR: 3
[106.028206][T276] this type is not correct!
[106.338327][T1] init: starting service 'vendor.gnss_service'...
[106.410848][T1] init: Service 'vendor.gnss_service' (pid 2920) exited with status 1
[106.419832][T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2920) process group...
07-06 07:15:10.253 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
[106.429802][T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2920 in 0ms
07-06 07:15:10.274 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:11.275 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:11.296 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:12.298 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:12.319 509 1840 D ATC : AT< +CME ERROR: 3
[109.035195][T276] this type is not correct!
07-06 07:15:13.320 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:13.341 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:14.343 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:14.364 509 1840 D ATC : AT< +CME ERROR: 3
[111.355466][T1] init: starting service 'vendor.gnss_service'...
[111.427602][T1] init: Service 'vendor.gnss_service' (pid 2921) exited with status 1
[111.435854][T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2921) process group...
[111.445884][T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2921 in 0ms
07-06 07:15:15.365 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:15.386 509 1840 D ATC : AT< +CME ERROR: 3
[112.042261][T276] this type is not correct!
07-06 07:15:16.388 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:16.409 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:17.410 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:17.431 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:18.432 509 535 D ATC : AT> at+qcfg="modemrstlevel",0
07-06 07:15:18.454 509 1840 D ATC : AT< +CME ERROR: 3
[115.049328][T276] this type is not correct!
07-06 07:15:19.455 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:19.477 509 1840 D ATC : AT< +CME ERROR: 3
[116.371730][T1] init: starting service 'vendor.gnss_service'...
[116.435654][T247] type=1400 audit(1688627720.256:104): avc: denied { read } for comm="android.hardware" name="vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1
[116.445294][T1] init: Service 'vendor.gnss_service' (pid 2922) exited with status 1
[116.457510][T247] type=1400 audit(1688627720.256:105): avc: denied { write } for comm="android.hardware" name="vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1
[116.466150][T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2922) process group...
[116.487193][T247] type=1400 audit(1688627720.256:106): avc: denied { open } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1
[116.497537][T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2922 in 0ms
[116.519512][T247] type=1400 audit(1688627720.256:107): avc: denied { ioctl } for comm="android.hardware" path="/dev/binderfs/vndbinder" dev="binder" ino=6 ioctlcmd=0x6209 scontext=u:r:hal_gnss_default:s0 tcontext=u:object_r:vndbinder_device:s0 tclass=chr_file permissive=1

```
[ 116.553188][ T247] type=1400 audit(1688627720.256:108): avc: denied { map } for comm="android.ha
rdwar" path="/dev/binderfs/vndbinder" dev="binder" ino=6 scontext=u:r:hal_gnss_default:s0 tcontext=u:ob
ject_r:vndbinder_device:s0 tclass=chr_file permissive=1
07-06 07:15:20.478 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:20.499 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:21.500 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:21.522 509 1840 D ATC : AT< +CME ERROR: 3
[ 118.056325][ T276] this type is not correct!
07-06 07:15:22.523 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:22.544 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:23.546 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:23.567 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:24.568 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:24.590 509 1840 D ATC : AT< +CME ERROR: 3
[ 121.063395][ T276] this type is not correct!
[ 121.386546][ T1] init: starting service 'vendor.gnss_service'...
[ 121.459062][ T1] init: Service 'vendor.gnss_service' (pid 2923) exited with status 1
[ 121.467440][ T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2923) process group...
[ 121.477486][ T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2923 in 0ms
07-06 07:15:25.591 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:25.612 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:26.613 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:26.635 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:27.636 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:27.657 509 1840 D ATC : AT< +CME ERROR: 3
[ 124.070647][ T276] this type is not correct!
07-06 07:15:28.658 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:28.680 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:28.877 509 535 D SIGNAL_STRENGTH: requestSignalStrength:720 iradio_version = 5
07-06 07:15:28.877 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:15:28.900 509 1840 D ATC : AT< +COPS: 0,0,"Airtel",7
07-06 07:15:28.901 509 1840 D ATC : AT< +COPS: 0,1,"Airtel",7
07-06 07:15:28.902 509 1840 D ATC : AT< OK
07-06 07:15:28.902 509 535 D ATC : AT> AT+QENG="servingcell"
07-06 07:15:28.927 509 1840 D ATC : AT< +QENG: "servingcell","NOCONN","LTE","FDD",404,45,9
A1F,292,240,1,3,3,46F,-87,-10,-61,58,36
07-06 07:15:28.927 509 1840 D ATC : AT< OK
07-06 07:15:28.928 509 535 D ATC : AT> AT+COPS=3,0;+COPS?;+COPS=3,1;+COPS?
07-06 07:15:28.950 509 1840 D ATC : AT< +COPS: 0,0,"Airtel",7
07-06 07:15:28.951 509 1840 D ATC : AT< +COPS: 0,1,"Airtel",7
07-06 07:15:28.952 509 1840 D ATC : AT< OK
07-06 07:15:28.952 509 535 D CELL_INFO: parseServingCell_234G:711 LTE RSRP=-87
07-06 07:15:28.952 509 535 D ATC : AT> AT+CSQ
07-06 07:15:28.974 509 1840 D ATC : AT< +CSQ: 26,99
07-06 07:15:28.974 509 1840 D ATC : AT< OK
07-06 07:15:28.975 509 535 D RADIO_1_4: getSignalStrength_1_4:563 LTE RSRP = -87 RSRQ = -10
07-06 07:15:28.975 509 535 D RIL_SERVICE_1_4: currentSignalStrengthInd 1948
07-06 07:15:28.975 509 535 E RIL_SERVICE_1_4: currentSignalStrengthInd_1_4: radioService[0]->m
RadioIndication == NULL
07-06 07:15:28.975 509 535 E RIL_SERVICE_1_2: currentSignalStrengthInd_1_2: radioService[0]->m
RadioIndication == NULL
07-06 07:15:28.975 509 535 E RIL_SERVICE_1_1: currentSignalStrengthInd: radioService[0]->mRadio
Indication == NULL
07-06 07:15:28.975 509 535 I RILC : RIL_SOCKET_1 UNSOLICITED: UNSOL_SIGNAL_STRENGT
H length:108
```

```
07-06 07:15:29.681 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:29.702 509 1840 D ATC : AT< +CME ERROR: 3
[ 126.403064][ T1] init: starting service 'vendor.gnss_service'...
[ 126.474702][ T1] init: Service 'vendor.gnss_service' (pid 2924) exited with status 1
[ 126.482866][ T1] init: Sending signal 9 to service 'vendor.gnss_service' (pid 2924) process group...
[ 126.493579][ T1] libprocessgroup: Successfully killed process cgroup uid 1021 pid 2924 in 0ms
```

```
07-06 07:15:30.703 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:30.724 509 1840 D ATC : AT< +CME ERROR: 3
[ 127.077721][ T276] this type is not correct!
07-06 07:15:31.725 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:31.746 509 1840 D ATC : AT< +CME ERROR: 3
07-06 07:15:32.748 509 535 D ATC : AT> at+qcfg="dbgctl",1
07-06 07:15:32.769 509 1840 D ATC : AT< +CME ERROR: 3
```

^C

```
130|mek_8q:/ # [ 130.084880][ T276] this type is not correct!
```